QuickSPOT™ 960 VMO - Vehicle Mount Self-deploying Satellite Antenna System

960 VMO - 96 cm Vehicle Mount Antenna & Baseband Product Specifications

Included Standard:

Auto-deploying antenna
8W Ku-band BUC (also available in 4W and extended-ku)
Antenna controller
Satellite modem
DVB receiver
LAN switch
30 ft IFL cables
Vehicle mounts
Baseband components integrated in rugged, shock mounted case

Overview

QuickSPOT's 96 cm Vehicle Mount Antenna makes establishing communications links easy. Within minutes of arrival a single operator can be on air. QuickSPOT antennas automatically deploy and lock on the satellite at the touch of a button. Automated login into the OnDemand network lets you launch any IP based application within seconds.

96 cm Vehicle Mount Antennas can be mounted temporarily on almost any van or SUV with a factory luggage rack easily and without modification to the vehicle. Permanent mount is available on flat roof vehicles. Drive safely at highway speeds with the antenna stowed.

Use this antenna for broadcast quality MPEG 4 video or large data connections throughout the continental US. Power can be supplied with an inverter on the vehicle or with a small generator.

Technical Specifications

Antenna			
Reflector	96 cm Ku-band round		
Optics	Prime focus offset		
Az/El/Pol Drive System	Roto-lok 3 axis positioner		
	Transmit		**Receive**
Frequency	13.75 - 14.5 Ghz		10.70 - 12.75 Ghz
Gain ± .2dBi	41.2 dB@ 11.95 Ghz		39.7 dBi
Polarization	Rotation of feed		
Cross-Pol Isolation	Std. Feed	Opt. Feed	
On-Axis	30 dB	35 dB	35 dB
Off-Axis	28 dB	28 dB	32 dB
Travel	Azimuth	± 200° from stow position	
	Polarization	± 95°	
Satellite Approval	Intelsat's worldwide fleet of Ku-band satellites		
Base pitch offset correction	±10° either axis		
Physical Data			
Approx. Weight	From 100 lbs + w/o BUC & LNB		
Max Length w/ IFL cables connected	68.3"		
Antenna Height	Stowed	19"	
	Deployed	55"	
Power consumption	Motors active	250 W	
Mount	Vehicle mount on Thule racks		
Controller	One Button Deploy; automatic satellite acquisition; peaking & cross-pol adjustment. One Button Stow		
Controller power	110/220 VAC, single-phase, 50/60 Hz		
Baseband System			
Power requirements	110/220 VAC, single-phase, 50/60 Hz		
Data rate capabilities	64 kbps to 4.5+ MB		
Satellite Access Methods	TDMA, SCPC, DVB/RCS		
Transmit Protocol	Automatic		
Std. Baseband Case – 4RU	Weight	Approx. 80 lbs	
	Dimensions	28" x 28" x 16"	

Proudly presented by
On Call Communications
19631 Descartes
Foothill Ranch, CA 92610
www.quickspot.net

Contact us today to learn how we can meet your mobile communications needs.
Tel +1 949 716-3030
Fax +1 949 588 1250
sales@quickspot.net